300 SERIES EXHAUST REELS



300 SERIES :: REEL SPECIFICATIONS

DESIGN

- Exhaust hose reel designed to enable the extraction of exhaust fumes directly from the source of their emission & maintain safer shop air quality.
- 15.2 cm exhaust ductwork on all models
- · For floor, wall & overhead mounting applications
- · Easy access panel to the drum for convenient routine maintenance
- · Hose guide rail
- · Internal ducting is included

STRUCTURE

- · Reel features an all welded steel frame, no bolts, for strength & durability
- · Drum mounted hose guide

RETRACTION

- · Enclosed factory tuned & matched cartridge-style spring motor
- · Cast iron lock ring with non-sparking bronze pawl
- · Multi-position lock ratchet mechanism secures hose at desired length.

SIGNATURE FEATURES

- · Professional grade heavy duty steel construction
- Durable proprietary CPC[™] powder coat process
- · Rolled edges & ribbed discs provide strength & safety
- · Leading 2-year manufacturer's limited warranty
- · Made in the U.S.A. Sold & Supported Worldwide

POSSIBLE FIELDS OF APPLICATION

- · Indoor Vehicle Exhaust Removal System
- · Vehicle Manufacturing **Facilities**
- · Automotive Dealerships
- Automotive & Fleet Service Centers
- Garage Settings
- · Fire Stations

COXREELS® 300 Series "Exhaust" spring driven reels are there to provide ventilation where necessary. This heavy duty frame was built to provide strength, stability and durability. The 300 Series reels have features found on many of our reels like spun discs, welded


steel frame and enclose cartridge motor. These reels also feature an easy access panel to have access to the main drum with internal ducting included, making it ready to go.


EXHAUST REELS

| LESS HOSE | | | | | |
|-----------|------------|--------------|-----|------------|--|
| MODEL | I.D. mm | LENGTH m | Kg. | SIZE INDEX | |
| 319-424 | 10.2 | 7 Capacity | 47 | 1 | |
| 328-440 | 10.2 | 12 Capacity | 52 | 2 | |
| 319-520 | 12.7 | 6 Capacity | 47 | 1 | |
| 328-532 | 12.7 | 10 Capacity | 52 | 2 | |
| 332-536 | 12.7 | 11 Capacity | 55 | 3 | |
| 319-620 | 15.2 | 6 Capacity | 48 | 1 | |
| 328-632 | 15.2 | 10 Capacity | 53 | 2 | |
| 332-636 | 15.2 | 11' Capacity | 123 | 3 | |

REEL DIMENSIONS Technical Data Sheets Available On Website

| SIZE INDEX | W mm | H mm | L mm | X mm | Y mm | Ø mm | Dw mm |
|------------|--------------------|---------|---------|---------|---------|---------|----------|
| 1 | 718 | 749 | 610 | 591 | 356 | 457 | 483 |
| 2 | 946 | 749 | 610 | 819 | 356 | 457 | 711 |
| 3 | 1048 | 749 | 610 | 921 | 356 | 457 | 813 |
| | Overall Dimensions | | | Base — | | Drum — | |





COXREELS® 300 FEATURES

Easy Access Panel

· An easy to remove panel allows full access to the drum

All Welded Steel Frame

• An all welded steel frame for strength, durability, stability & to prevent tip-overs

PERFECT FOR:

Repair Centers Fire Stations Service Station Smog Stations Emergency Crews



