

SPRING DRIVEN FUEL HOSE REELS DEF SERIES & FUELING REELS


COXREELS® DEF Series are equipped with a stainless steel external full-flow swivel and chemical resistant Viton® seals to provide a safe, reliable Diesel Exhaust Fluid (DEF) dispensing solution. The swivel is easy to access for simple seal maintenance and fast DEF dispenser hose installation. Coxreels® professional DEF reeling systems are available in heavy-duty single pedestal (SH Series) or supreme-duty dual pedestal (T Series) configurations. Both versatile designs are outfitted with Coxreels' original Super Hub™ dual axle support systems to increase stability and reduce vibration during operation, making these reels the perfect DEF handling solutions for either stationary or rugged mobile applications.

DEF-SH SERIES MODELS

Models are equipped with DEF hose **Note: Do not exceed listed hose O.D. to obtain maximum length.**

HOSE							LESS HOSE		SIZE INDEX
MODEL	I.D. mm	O.D. mm	LENGTH m	BAR	Kg.	AVAILABLE IN EZ-COIL	MODEL	Kg.	
-	13	22	15	21	-	-	*SHL-N-450-BBX	21	2
SH-N-525-DF-BBX	19	29	8	21	26	EZ-SH-525-DF-BBX	SHL-N-525-BBX	20	3
SH-N-550-DF-BBX	19	29	15	21	34	EZ-SH-550-DF-BBX	SHL-N-550-BBX	25	6

*EZ-Coil® option only available on these less hose models. Please add prefix "EZ-"



DEF-T SERIES MODELS

Models are equipped with DEF hose **Note: Do not exceed listed hose O.D. to obtain maximum length.**

HOSE							LESS HOSE		SIZE INDEX
MODEL	I.D. mm	O.D. mm	LENGTH m	BAR	Kg.	AVAILABLE IN EZ-COIL	MODEL	Kg.	
-	13	22	15	21	-	-	*TSHL-N-450-BBX	25	1
-	19	29	11	21	-	-	*TSHL-N-535-BBX	30	3
TSH-N-550-DF-BBX	19	29	15	21	41	EZ-TSH-550-DF-BBX	TSHL-N-550-BBX	32	3
-	25	35	11	21	-	-	TSHL-N-635-BBX	32	5
-	25	35	15	21	-	-	TSHL-N-650-BBX	35	4

*EZ-Coil® option only available on these less hose models. Please add prefix "EZ-"

COXREELS® Fuel Dispensing Reels are designed to handle various non-aromatic fuel applications including diesel, kerosene, fuel oil and heating oil. Coxreels® professional fuel dispensing reels are available in heavy-duty single pedestal (SH Series), supreme-duty dual pedestal (T Series) or box-style frame (SP Series) configurations. These fuel reels are an essential component found in utility, ground support, and bulk liquid handling transport services mounted on fuel storage & dispensing systems, fuel/lube trucks, aircraft refuelers, and tank trucks. The convenient uncoiling systems with the added hose control allow the operator to efficiently handle fuel transfers.

FUEL HOSE SH SERIES

Models are equipped with fuel hose **Note: Do not exceed listed hose O.D. to obtain maximum length.**

HOSE							LESS HOSE		SIZE INDEX
MODEL	I.D. mm	O.D. mm	LENGTH m	BAR	Kg.	AVAILABLE IN EZ-COIL	MODEL	Kg.	
SHF-N-525	19	21	8	21	26	EZ-SHF-525	*SHL-N-525-BXN	20	3

*EZ-Coil® option only available on these less hose models. Please add prefix "EZ-"

FUEL HOSE T SERIES

Models are equipped with fuel hose **Note: Do not exceed listed hose O.D. to obtain maximum length.**

HOSE							LESS HOSE		SIZE INDEX
MODEL	I.D. mm	O.D. mm	LENGTH m	BAR	Kg.	AVAILABLE IN EZ-COIL	MODEL	Kg.	
TSHF-N-550	19	21	15	21	41	EZ-TSHF-550	*TSHL-N-550-BXN	32	5
TSHF-N-575	19	21	23	21	48	-	TSHL-N-575-BXN	33	8
TSHF-N-635	25	38	11	21	43	-	TSHL-N-635-BXN	32	6
TSHF-N-650	25	38	15	21	46	-	TSHL-N-650-BXN	35	8

*EZ-Coil® option only available on these less hose models. Please add prefix "EZ-"

FUEL HOSE SP SERIES

Models are equipped with fuel hose **Note: Do not exceed listed hose O.D. to obtain maximum length.**

HOSE							LESS HOSE		SIZE INDEX
MODEL	I.D. mm	O.D. mm	LENGTH m	BAR	INLET/OUTLET N.P.T. mm	Kg.	MODEL	Kg.	
SLPF-550	19	21	15	21	47	107	SLPL-550	39	2
SLPF-650	25	38	15	21	64	142	SLPL-650	49	6

REEL DIMENSIONS Please see noted series page for designated SIZE INDEX reference

- See page 12 For DEF SH Series dim drawings
- See page 12 For Fuel Hose Equipped SH Series dim drawings
- See page 13 For DEF T Series dim drawings
- See page 13 for Fuel Hose Equipped T Series dim drawings
- See page 20 for Fuel Hose Equipped SP Series dim drawings

DEF & FUELING SERIES :: REEL SPECIFICATIONS

DEF SERIES SWIVEL

- Non-corrosive stainless steel 90° full flow NPT swivel for Diesel Exhaust Fluid (DEF) dispensing applications.
- Swivel seals: Viton®

DEF SERIES HOSE

- DEF dispensing hose designed to convey the high-purity, aqueous urea solution DEF. Temperature Range: -40°C to +125°C

FUEL SERIES SWIVEL

- Machined from solid brass 90° full-flow NPT swivel inlet for fuel dispensing applications. Electroless nickel plated steel swivel on 25 mm models
- Swivel seals: Nitrile

FUEL SERIES HOSE

- Fuel dispensing hose designed to convey non-aromatic fuels including diesel, kerosene, fuel oil & heating oil. Temperature Range: -28°C to +88°C

DESIGN & STRUCTURE

- Each of these reels is built of their standard series with their own unique features & benefits

RETRACTION

- See page 12 for SH Series spring driven features
- See page 13 for T Series spring driven features
- See page 20 for SP Series spring driven features

SIGNATURE FEATURES

- Professional grade heavy duty steel construction
- Durable proprietary CPC™ powder coat process
- Rolled edges & ribbed discs provide strength & safety
- Leading 2-year manufacturer's limited warranty
- Made in the U.S.A. - Sold & Supported Worldwide

POSSIBLE FIELDS OF APPLICATION

- Vehicle Refueling
- Tank Trucks
- Fuel/Lube Trucks
- Fuel Storage & Dispensing Systems
- DEF Storage & Dispensing Systems
- Aircraft Refueling
- Marine/Ship Refueling/Offshore

ACCESSORIZE YOUR REEL :: Pg 50

- O-Rings & Swivels
- Hoses
- Mounting Brackets
- Assorted Reel Accessories

