



MOUNTING & ROLLER BRACKETS

PART NO.	REEL SERIES								
	P	SH, MP & HP	T	C	EN	PC	P-W & SHW	P-WC	Alumi-Pro® Nitro-Pro®
 <p>Swing Bracket For vertical surface mounting, allows reel to swing 180°. Powder coated crinkle black 5 mm steel. Weight: 2 Kg.</p>	15720	•	•			•	•	•	•
	15725			•	•				
 <p>Swivel Bracket For horizontal surface mounting, ball bearing rotation, allows reel to swivel 345°. Powder coated crinkle black heavy gauge steel. Weight: 3 Kg. NOT FOR USE IN CEILING APPLICATIONS.</p>	15721	•	•	•	•	•	•	•	•
 <p>EZ-Up Bracket Reel easily slides in & out for easy overhead mounting. Use as an alternative to the #MR-1. Must be ordered with #15724 for "I" or "H" beam installations. Weight: 3 Kg.</p>	15723	•	•	•	•	•	•	•	•
 <p>EZ-Up "I" or "H" Beam Adapter Must be ordered with #15723. Powder coated crinkle black, all steel construction. Weight: 2 Kg.</p>	15724	•	•	•	•	•	•	•	•
 <p>Mounting Bracket For overhead mounting, fits 76 to 216 mm flange on "I" or "H" beam. Powder coated crinkle black 5 mm bent steel. Weight: 6 Kg.</p>	MR-1	•	•			•	•	•	•
	MRT-1			•	•				
 <p>4-Way Roller Bracket Heavy gauge steel, powder coated Corexels blue (4RB). Available in stainless steel (4RB-SS). Weight: 0.5 Kg.</p>	4RB 6 - 19mm	•	•	•	•	•	•	•	•
	4RB-SS 6 - 19mm	•	•	•	•	•	•	•	•

S SERIES MOUNTING & ROLLER BRACKETS

PART NO.	S SERIES MODELS			
	SR13 & SL13	SR15 & SL15	SR17 & SL17	SR19 & SL19
 <p>Dual Side Mount Bracket Heavy gauge steel, powder coated crinkle black. Weight: 2 Kg.</p>	15726-13	•		
	15726-15		•	
	15726-17			•
	15726-19			•
 <p>Single Side Mount Bracket Heavy gauge steel, powder coated crinkle black. Weight: 1 Kg.</p>	SMB1	•	•	
	SMB2			•
	SMB3			•

PVC INLET HOSE ASSEMBLIES

PART NO.	FITTINGS	I.D. mm	LENGTH m	BAR
5150-1.5	6 mm Male x Female NPT	6	5	21
5153-1.5	10 mm Male x Female NPT	10	5	21
5154-1.5	13 mm Male x Female NPT	13	5	21
5155-1.5	19 mm Male x Male NPT	19	5	21
5224-1.5	10 mm Male x Male NPT	10	5	207
5256-1.5	13 mm Male x Male NPT	13	5	172
5290-1.5	19 mm Male x Male NPT	19	5	103
5304-1.5	6 mm Male x Male NPT	6	5	345
5336-1.5	10 mm Male x Male NPT	10	5	276
15717	Garden 19 mm NPTM (w/ Part #10781) x 19 mm NPT	19	15	21
5423-1.5	Twin Grade R 3 mm NPTM x BB 9-16 UNF	6 mm Twin Line	5	14
5424-1.5	"T" Grade Twin Grade R 3 mm NPTM x BB 9-16 UNF	6 mm Twin Line	5	14

90° ELBOWS

PART NO.	FITTING THREAD	I.D. mm	BAR
6088	Brass LP Male x Female NPT	6	21
208	Brass LP Male x Female NPT	10	21
222	Brass LP Male x Female NPT	13	21
385	Brass LP Male x Female NPT	19	21
500	Steel MP Male x Female NPT	10	207
1671	Steel MP Male x Female NPT	13	207
15014	Steel MP Male x Female NPT	19	86
616	Steel HP Male x Female NPT	6	345
617	Steel HP Male x Female NPT	10	345

HOSE STOPS & GUARDS

HOSE STOPS PART NO.	HOSE GUARD PART NO.	HOSE		OVERALL cm
		I.D. mm	O.D. mm	
131	237-1	6	13	6.4
633	237-1	6 mm Twin Line		8.9
131-3	237-1	10	17	6.4
131-4	398-1	13	19	6.4
254	-	13	19	8.9
430	398-1	19	25	8.9
20214	-	25	40	12.7
20215	-	32	46	12.7
20216	-	38	52	12.7
20217	-	51	65	12.7

BEND RESTRICTORS

ADD SUFFIX	I.D. mm	DESCRIPTION	BAR
-BXB	6	Black PVC Bend Restrictor	21
-BXB	10	Black PVC Bend Restrictor	21
-BXB	13	Black PVC Bend Restrictor	21

Designed to limit the degree of bending without compromising the integrity of the hose assembly while also preventing the hose-end from kinking, excessive wearing, and tearing.

QUICK DISCONNECTS

PART NO.	I.D. mm	DESCRIPTION	CONNECTION	BAR
10759-1	6	Quick Disconnect	NPT (F)	21
10759-2	10	Quick Disconnect	NPT (F)	21

Quick disconnect couplings thread onto end of hose fitting to provide fast, leak-proof connections for low pressure hose lines. Conveniently connect, interchange, and secure pneumatic tools or other spraying devices to any air, water, chemical or other hose lines.

SPRING DRIVEN