SD & SDH SERIES STATIC DISCHARGE CABLE REELS

EZ-SD Series

SDH Series

COXREELS® SD and SDH Series "Static Discharge" cable reels are built heavy duty and designed for long lasting performance. They are specifically design to be used in combustible environments where the static buildup could ignite a spark and subsequent explosion. Static discharge or grounding reels are commonly paired with fuel hose reels found on page 33.

SPRING STATIC DISCHARGE REELS WITH GALVANIZED CABLE

WITH GALVANIZED CABLE					LESS CABLE		SIZE INDEX
MODEL	FT.	O.D.	APRX. LBS.	AVAILABLE IN EZ-COIL	MODEL	APRX. LBS.	
SD-35	35	5/32"	18	**EZ-SD-35**	-	-	**1**
SD-50	50	5/32"	20	**EZ-SD-50**	**SDL-50**	18	**1**
SD-75	75	5/32"	31	**EZ-SD-75**	-	-	**2**
SD-100	100	5/32"	32	**EZ-SD-100**	**SDL-100**	28	**2**

To order EZ-Coil® equipped models less hose, please add prefix "EZ-"

SPRING STATIC DISCHARGE REELS WITH STAINLESS STEEL CABLE

WITH STAINLESS STEEL CABLE					LESS CABLE		SIZE INDEX
MODEL	FT.	O.D.	APRX. LBS.	AVAILABLE IN EZ-COIL	MODEL	APRX. LBS.	
SD-35-1	35	5/32"	18	**EZ-SD-35-1**	-	-	**1**
SD-50-1	50	5/32"	20	**EZ-SD-50-1**	**SDL-50**	18	**1**
SD-75-1	75	5/32"	31	**EZ-SD-75-1**	-	-	**2**
SD-100-1	100	5/32"	32	**EZ-SD-100-1**	**SDL-100**	28	**2**

To order EZ-Coil® equipped models less hose, please add prefix "EZ-"

HAND CRANK STATIC DISCHARGE REELS WITH GALVANIZED CABLE

WITH GALVANIZED CABLE				LESS CABLE		SIZE INDEX
MODEL	FT.	O.D.	APRX. LBS.	MODEL	APRX. LBS.	
SDH-100	100	5/32"	24	-	-	**3**
SDH-200	200	5/32"	28	**SDHL-200**	20	**3**

HAND CRANK STATIC DISCHARGE REELS WITH STAINLESS STEEL CABLE

WITH GALVANIZED CABLE				LESS CABLE		SIZE INDEX
MODEL	FT.	O.D.	APRX. LBS.	MODEL	APRX. LBS.	
SDH-100-1	100	5/32"	24	-	-	**3**
SDH-200-1	200	5/32"	28	**SDHL-200**	20	**3**

REEL DIMENSIONS

Technical Data Sheets Available On Website

SIZE INDEX	W	H	L	X	Y	N
1	3 7/8"	11 1/2"	11"	2 1/2"	6"	4"
2	4"	15"	14 1/2"	2 1/2"	6"	4"
3	5 3/4"	11 1/2"	11"	2 1/2"	6"	4"
	Overall Dimensions			Base		Mounting Pattern

SD Series



SDH Series



SPRING DRIVEN

SD & SDH SERIES :: REEL SPECIFICATIONS

STATIC DISCHARGE

- Available with 7 strand x 7 wire galvanized steel or stainless steel cable
- High visibility orange vinyl cable cover
- Includes cable, ball stop & 50 Amp grounding clamp (100 Amp copper grounding clamp available, consult factory)

DESIGN & STRUCTURE

- Compact static discharge cable reel available in spring rewind or direct hand crank retraction
- Commonly paired with fuel reels & used in combustible environment for grounding purposes
- Guide arm adjusts to wall, floor, vehicle & overhead positions
- Solid one piece, heavy gauge 1/4" steel base for maximum stability
- 1" solid steel axle & lubricated precision bearings for smooth rotation
- Bottom of base is un-powder coated to ground reel

RETRACTION

- Controlled retraction speed up to 80% slower on EZ-COIL models :: See page 7 for details
- Enclosed factory tuned & matched cartridge-style spring motor on SD Series
- Non corrosive stainless steel spring, pawl & zinc plated ratchet on SD Series
- Multi-position non-sparking lock ratchet mechanism secures cable at desired length on SD Series
- Simple design with direct hand crank action on SDH Series

SIGNATURE FEATURES

- Professional grade heavy duty steel construction
- Durable proprietary CPC™ powder coat process
- Rolled edges & ribbed discs provide strength & safety
- Leading 2-year manufacturer's limited warranty
- Made in the U.S.A. - Sold & Supported Worldwide

POSSIBLE FIELDS OF APPLICATION

- Fuel / Service Trucks
- Fuel Storage & Dispensing Systems
- Ground Support
- Aviation Static Grounding
- Aviation Refueling
- Vehicle Refueling
- Marine / Ship Refuiling / Offshore
- Oil Refinery

ACCESSORIZE YOUR REEL :: PG 50

- Mounting Brackets
- Assorted Reel Accessories